

## DS-8004HSI-S Standalone DVR



### Key Features

- Each channel supports up to 4CIF encoding
- Video loop output interface
- 4 SATA interface
- eSATA interface for high-speed backup (optional)

### Specifications

#### Video/Audio Input

Video Compression	H.264
Video Input	4
Video Input Interface	BNC (1.0Vp-p, 75Ω)

#### Hard Disk Drive

Interface	SATA x 4
Capacity	Each HDD Supports Up to 2000GB

#### Video/Audio Output

Display	PAL: 704x576 NTSC: 704x480
Recording Resolution	4CIF/DCIF/2CIF/CIF/QCIF
Video Loop Output	4
Video Output	1 channel, BNC (1.0Vp-p, 75Ω)
Recording/Playback	4CIF: 8fps DCIF: 8fps 2CIF: 15fps CIF: 25(P)/30(N)fps
Bit Rate	32Kbps ~ 8Mbps
VGA Output	1, Support 800x600 (60Hz), 1024x768 (60Hz), 1280x1024 (60Hz)

#### External Interface

Communication Interface	1 RJ45 10M/100M Ethernet Port
	1 RJ45 RS232 Port
RS-485 Port	1 Port (T+, T-, R+, R-)
Keyboard Interface	2 RJ45
USB Interface	1
Alarm Input	4 (Terminal Block)
Alarm Output	2 (Terminal Block)

#### General

Power Supply	100~240VAC, 6.3A, 50~60Hz
Power Consumption	≤70W (w/o HDD and DVD-R/W)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Chassis	19" Standard
Dimensions	470mm(D)x441mm(W) x90mm(H)
Weight	≤8Kg (w/o HDD and DVD-R/W)

## DS-8008HSI-S Standalone DVR



### Key Features

- Each channel supports up to 2CIF encoding
- Video loop output interface
- 8 SATA interface
- eSATA interface for high-speed backup (optional)

### Specifications

#### Video/Audio Input

Video Compression	H.264
Video Input	8
Video Input Interface	BNC (1.0Vp-p, 75Ω)

#### Hard Disk Drive

Interface	SATA x 8
Capacity	Each HDD Supports Up to 2000GB

#### Video/Audio Output

Display	PAL: 704x576 NTSC: 704x480
Recording Resolution	2CIF/CIF/QCIF
Video Loop Output	8
Video Output	1 channel, BNC (1.0Vp-p, 75Ω)
Recording/Playback	2CIF: 8fps CIF: 25(P)/30(N)fps
Bit Rate	32Kbps ~ 8Mbps
VGA Output	1, Support 800x600 (60Hz), 1024x768 (60Hz), 1280x1024 (60Hz)

#### External Interface

Communication Interface	1 RJ45 10M/100M Ethernet Port 1 RJ45 RS232 Port
RS-485 Port	1 Port (T+, T-, R+, R-)
Keyboard Interface	1 Port (D+, D-)
USB Interface	1
Alarm Input	16 (Terminal Block)
Alarm Output	4 (Terminal Block)

#### General

Power Supply	100~240VAC, 6.3A, 50~60Hz
Power Consumption	≤70W (w/o HDD and DVD-R/W)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Chassis	19" Standard
Dimensions	470mm(D)x441mm(W) x90mm(H)
Weight	≤8Kg (w/o HDD and DVD-R/W)

## DS-8016HSI-S Standalone DVR



### Key Features

- Each channel supports up to 2CIF encoding
- Video loop output interface
- 8 SATA interface
- eSATA interface for high-speed backup (optional)

### Specifications

#### Video/Audio Input

Video Compression	H.264
Video Input	16
Video Input Interface	BNC (1.0Vp-p, 75Ω)

#### Hard Disk Drive

Interface	SATA x 8
Capacity	Each HDD Supports Up to 2000GB

#### Video/Audio Output

Display	PAL: 704x576 NTSC: 704x480
Recording Resolution	2CIF/CIF/QCIF
Video Loop Output	16
Video Output	1 channel, BNC (1.0Vp-p, 75Ω)
Recording/Playback	2CIF: 8fps CIF: 25(P)/30(N)fps
Bit Rate	32Kbps ~ 8Mbps
VGA Output	1, Support 800x600 (60Hz), 1024x768 (60Hz), 1280x1024 (60Hz)

#### External Interface

Communication Interface	1 RJ45 10M/100M Ethernet Port 1 RJ45 RS232 Port
RS-485 Port	1 Port (T+, T-, R+, R-)
Keyboard Interface	1 Port (D+, D-)
USB Interface	1
Alarm Input	16 (Terminal Block)
Alarm Output	4 (Terminal Block)

#### General

Power Supply	100~240VAC, 6.3A, 50~60Hz
Power Consumption	≤70W (w/o HDD and DVD-R/W)
Operating Temperature	-10°C ~ 55°C
Humidity	10% ~ 90%
Chassis	19" Standard
Dimensions	470mm(D)x441mm(W) x90mm(H)
Weight	≤8Kg (w/o HDD and DVD-R/W)